Glass Door Refrigerators

Stainless Steel Interior Digitally Controlled Uniform Temperature







___ FEATURES / BENEFITS =__

■ DIGITAL TEMPERATURE CONTROL SYSTEM

Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.

High-Tech Monitor

The unit will beep if the door has been opened for more than 30 seconds. The monitor digitally displays the present temperature and current status of the refrigerator. You can easily change the temperature by adjusting the thermostat.

■ EFFICIENT REFRIGERATION SYSTEM

Turbo Air's glass door refrigerators are designed with over-sized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

■ AUTOMATIC EVAPORATOR FAN MOTOR DELAYS

Through stopping the evaporator fan when the refrigerator door opens, the circulation of hot, moist air into the refrigerator is prevented. This increases energy efficiency and lengthens the life of the compressor.

■ STAINLESS STEEL INTERIOR & EXTERIOR WITH AL SIDES

The Turbo Air New Maximum model is constructed with stainless steel top & bottom grilles and clear aluminum coated side panels. The door is glass with AL frame. The interior is stainless steel that guarantees the utmost in cleanliness and long product life. The New Maximum can add a touch of style to the most refined setting.

■ ADJUSTABLE, HEAVY DUTY, PE(POLYETHYLENE) COATED WIRE SHELVES

■ HIGH-DENSITY POLYURETHANE INSULATION

Entire cabinet structure is formed-in-place using high density, CFC free polyurethane insulation.

ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. Self-closing features make this the ultimate choice in customer convenience.

■ DOUBLE PANE GLASS DOORS WITH HEAT REFLECTING FILM

Equipped with unique double pane glass doors with a layer of patented, transparent thermal insulating film applied between the two glass layers. Light weight door construction reduces door maintenance.

■ MAGNETIC DOOR GASKETS

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

BOTTOM MOUNT COMPRESSOR UNITS

Turbo Air's bottom mount compressor allows easier access for service and extra storage space above. In addition, the lower area provides a cooler and less greasy operating environment which results in reduced compressor running time.

■ REFRIGERATOR HOLDS 34°F ~ 39°F FOR THE BEST IN FOOD PRESERVATION

Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight	LDH
MSR-23G-1	1	23	3	1/4	5.3	310	27 x 303/4 x 781/4
MSR-49G-2	2	49	6	1/3	7	480	543/8 x 303/4 x 781/4
MSR-72G-3	3	72	9	2/3	11	680	817/8 x 303/4 x 781/4

^{*} Height does not include 6" for caster height. * Depth does not include 1-1/2" for glass door handles.

ELECTRICAL DATA	MSR-23G-1	MSR-49G-2	MSR-72G-3
Voltage (1) NEMA-5-15P	①115/60/1	①115/60/1	①115/60/1
Amp	5.3 A	7 A	11 A
Compressor (HP)	1/4	1/3	2/3
Feed Wires (with ground)	3	3	3
Cord Length (ft.)	7	7	7
DIMENSIONAL DATA			
# of Doors	1	2	3
Cubic Feet	23	49	72
# of Racks Accepted	1	2	3
Length Overall (in)	27	543/8	817/8
Depth Overall (in)	303/4	303/4	303/4
Height Overall (in)	781/4	781/4	781/4
Interior Dimension (LxDxH)	23x243/4x603/8	501/2x243/4x603/8	78x243/4x603/8
Shelf Size	215/8x231/4	243/8x231/4	243/8x231/4
# of Shelves	3 ea	6 ea	9 ea

^{*}Design and specifications subject to change without notice.

- FLUORESCENT INTERIOR LIGHTING
- Door Locks
- SELF-CONTAINED SYSTEM
- 4" SWIVEL CASTERS
- SOLID AND STURDY GRILLE DESIGN
- LEGS AVAILABLE FOR ALL MODELS (OPTIONAL)
- TRAY RACK AVAILABLE (OPTIONAL)
 All models accept full size door tray racks.
- REMOTE CABINETS AND CONDENSING UNITS AVAILABLE FOR ALL MODELS.

■ WARRANTY: 1 Year Labor and Parts Warranty
Additional 4 Years Warranty on Compressor

(unit: inch)



