

# Solid Door Refrigerators

Exceptional Quality 2 Years Parts and Labor Warranty



## FEATURES / BENEFITS

- DIGITAL TEMPERATURE CONTROL SYSTEM**  
 Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.
- HIGH-TECH MONITOR**  
 The unit will beep if the door has been opened for more than 30 seconds. The monitor digitally displays the present temperature and current status of the refrigerator. You can easily change the temperature by adjusting the thermostat.
- EFFICIENT REFRIGERATION SYSTEM**  
 Turbo Air's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.
- AUTOMATIC EVAPORATOR FAN MOTOR DELAYS**  
 Through stopping the evaporator fan when the refrigerator door opens, the circulation of hot, moist air into the refrigerator is prevented. This increases energy efficiency and lengthens the life of the compressor.
- STAINLESS STEEL CABINET CONSTRUCTION**  
 The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (except the back). It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury. The Super Deluxe can add a touch of style to the most refined setting.
- STURDY, CLEAN STAINLESS SHELVING**  
 Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless shelving.
- HIGH-DENSITY POLYURETHANE INSULATION**  
 The entire cabinet structure and solid doors are formed-in-place using high density, CFC free polyurethane insulation.
- ERGONOMICALLY DESIGNED DOORS**  
 Customers' fatigue fades away with easy grip handles and doors that open effortlessly. Self-closing and stay open door features make this the ultimate choice in customer convenience.
- MAGNETIC DOOR GASKETS**  
 Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.
- BOTTOM MOUNT COMPRESSOR UNITS**  
 Turbo Air's bottom mount compressor allows easier access for service and extra storage space above. In addition, the lower area provides a cooler and less greasy operating environment which results in reduced compressor running time.
- LEFT HINGED MODEL AVAILABLE**
- REFRIGERATOR HOLDS 33°F ~ 38°F FOR THE BEST IN FOOD PRESERVATION**

Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight	L D H
TSR-23SD	1	23	3	1/4	5.5	274	27 x 30 3/8 x 78 1/4
TSR-35SD	2	35	6	1/3	9	357	39 1/2 x 30 3/8 x 78 1/4
TSR-49SD	2	49	6	1/3	9.2	427	54 3/8 x 30 3/8 x 78 1/4
TSR-72SD	3	72	9	1/2	11.3	602	81 7/8 x 30 3/8 x 78 1/4

\* Height does not include 6" for caster height.

# TSR MODELS SPECIFICATIONS

ELECTRICAL DATA	TSR-23SD	TSR-35SD	TSR-49SD	TSR-72SD
Voltage (NEMA-5-15P)	115/60/1	115/60/1	115/60/1	115/60/1
Amp	5.5A	9A	9.2A	11.3A
Compressor (HP)	1/4	1/3	1/3	1/2
Feed Wire (with ground)	3	3	3	3
Cord Length (ft.)	9	9	9	9
DIMENSIONAL DATA				
# of Doors	1	2	2	3
Cubic Feet	23	35	49	72
# of Racks Accepted	1	2	2	3
Length Overall (in)	27	39 1/2	54 3/8	81 7/8
Depth Overall (in)	30 3/8	30 3/8	30 3/8	30 3/8
Height Overall (in)	78 1/4	78 1/4	78 1/4	78 1/4
Interior Dimension (LxDxH)	23x24 3/4x60 3/8	35 5/8x24 3/4x60 3/8	50 1/2x24 3/4x60 3/8	77 7/8x24 3/4x60 3/8
Shelf Size	21 5/8x23 1/4	17 1/4x23 1/4	24 3/8x23 1/4	24 3/8x23 1/4
# of Shelves	3 ea	6 ea	6 ea	9 ea

- INCANDESCENT INTERIOR LIGHTING
- DOOR LOCKS
- SELF-CONTAINED SYSTEM
- 4" SWIVEL CASTERS
- SOLID AND STURDY GRILLE DESIGN
- LEGS AVAILABLE FOR ALL MODELS (OPTIONAL)
- TRAY RACK AVAILABLE (OPTIONAL)  
All models accept full size tray racks.
- REMOTE CABINETS AND CONDENSING UNITS AVAILABLE FOR ALL MODELS.

\*Design and specifications subject to change without notice.

- **WARRANTY : 2 Years Labor and Parts Warranty**  
**Additional 3 Years Warranty on Compressor**

(unit : inch)

